

# MAXHUB Interactive Flat Panel U3 Series

MAXHUB U3 Series shines as an exceptional choice, tailored specifically for educational environments. It features a secure operating system for seamless integration with Google apps and accounts. The AI-powered SoC ensures smooth performance, while the advanced touchscreen allows for natural and precise writing. With versatile connectivity options, teachers can easily share content from multiple devices. MAXHUB U3 Series enhances classroom collaboration and engagement, making it the perfect choice for educators and students.



## Prominent Display

High color accuracy,  $\Delta E \leq 1.5$   
500 nits Peak brightness



## Precise Touch

Revolutionary writing experience,  
near-zero latency




## Classroom Care

Eye care and anti-bacterial  
certifications




## Immersive Sound

2.2 Channel speaker  
8-Array microphone



## Peak Performance

AI-Powered 8-core CPU  
8GB RAM, 64GB ROM



## Unparalleled Compatibility

Latest Android 13 system,  
Google EDLA certificated



## Convenient Connectivity

Full function USB-C, integrate  
100W PD, video, audio, touch  
and internet access features



## Comprehensive Software Suite

MAXHUB EDU OS V4.0, extensive  
self-developed applications

<b>Display</b>			
Model	U6530	U7530	U8630
Diagonal Size (inch)	65	75	86
Display Area	1428.48(H)×803.52(V)mm	1650.24(H)×928.26(V)mm	1895.04(H)×1065.96(V)mm
Aspect Ratio	16:9	16:9	16:9
Resolution	3840(H)×2160(V)	3840(H)×2160(V)	3840(H)×2160(V)
Panel Type	VA	VA	VA
Viewing Angle	178° (H/V)	178° (H/V)	178° (H/V)
Screen Level	A-Level	A-Level	A-Level
Panel Brightness	450 nits	500 nits	500 nits
Contrast Ratio	5,000:1 (Typ.) 50,000:1 (Dynamic)	5,000:1 (Typ.) 50,000:1 (Dynamic)	5,000:1 (Typ.) 50,000:1 (Dynamic)
Color Depth	1.07B (10bit)	1.07B (10bit)	1.07B (10bit)
Color Gamut (typ.)	72% NTSC	72% NTSC	72% NTSC
Color Accuracy	Delta E ≤ 1.5	Delta E ≤ 1.5	Delta E ≤ 1.5
Glass	Zero parallax 3mm Thickness 9H Tempered	Zero parallax 3mm Thickness 9H Tempered	Zero parallax 3mm Thickness 9H Tempered
Surface Technology	Non-glare Technology	Non-glare Technology	Non-glare Technology
Sensor	Ambient light sensor Ambient color temperature sensor	Ambient light sensor Ambient color temperature sensor	Ambient light sensor Ambient color temperature sensor
Eyes Care	TÜV Flicker Free TÜV Low Blue Light	TÜV Flicker Free TÜV Low Blue Light	TÜV Flicker Free TÜV Low Blue Light
Anti-bacterial	TÜV/SGS/SIAA Anti-bacterial certifications	TÜV/SGS/SIAA Anti-bacterial certifications	TÜV/SGS/SIAA Anti-bacterial certifications
Refresh Rate	60Hz	60Hz	60Hz
Response Time	6.5ms	6.5ms	6.5ms
Backlight Unit	DLED	DLED	DLED
Backlight Life (typ.)	≥50,000 Hours	≥50,000 Hours	≥50,000 Hours

<b>POWER</b>			
Power Supply	100-240V~50/60Hz 4.0A	100-240V~50/60Hz 4.0A	100-240V~50/60Hz 4.0A
Power Consumption (standby)	≤ 0.5W	≤ 0.5W	≤ 0.5W
Power Consumption (typ.)	195W	320W	375W

<b>Physical Specification</b>			
Dimension (L×H×D)	1488×908×86mm	1709.4×1031×85.7mm	1957×1171×86mm
Shipping Dimension (L×H×D)	1628×1005×208mm	1863×1148×225mm	2110×1291×225mm
Thickness of Machine and Wall Mount	116mm (WIB9060G)	116mm (WIB9060G)	116mm (WIB9060G)
Wall-hanging Screw	M8×25mm	M8×25mm	M8×25mm
VESA	600×400mm	800×400mm	800×600mm
Net Weight	38.67kg	51.46kg	63.55kg
Gross Weight	48.25kg	60.75kg	80.15kg

<b>Touch System</b>	
Touch Technology	Intelligent Touchscreen Technology (infrared recognition)
Touch Point	50 Points touch
Object Recognition Range	1.5mm
Accuracy	±0.5mm
Response Time	≤2.5ms
Writing Height	≤1mm
System (Touch Return)	Windows11/Windows10/Windows8/Windows7/Android/Linux/Mac OS X/Chrome

<b>Audio</b>	
Built-in Microphone	8-Microphone array
Microphone Pick Up Range	0~10m
Sound Channel	2.2
Speaker	2×8W+2×18W Outputs 2×12W+2×25W Maximum

Connectivity		
Input	HDMI IN × 4	Up to 4K@60Hz, HDCP 2.3, CEC
	USB 2.0 × 1	For system upgrades
Output	USB 3.0 × 4	Front×2, Rear×2
	USB Type-C × 2	Video, Audio, Touch, Charge, LAN Network Sharing
Input	DP IN × 1	Front: Up to 100W PD, Rear: Up to 15W PD
	AUDIO IN × 1	4K@30Hz, HDCP 1.4&2.3
Output	RS232 × 1	3.5mm Jack
	RJ45 IN × 1	Baud rate 9600
Output	HDMI OUT × 1	10M/100M/1000Mbps
	USB Type-C × 1	Up to 4K@60Hz
Output	TOUCH OUT × 2	4K@60Hz
	AUDIO OUT × 1	Touch 2.0
Output	SPDIF × 1	3.5mm Jack
	RJ45 OUT × 1	PCM output format
OPS Slot	Module slot × 1	10M/100M/1000Mbps
Wi-Fi Slot	Module slot × 1	
Wi-Fi	Wi-Fi 6 supported	
Bluetooth	802.11ac/b/g/n/a/ax, 2.4GHz/5GHz	
	5.2	

Built-in System		Accessories	
Operating System	Android 13.0	Power Cord	3m×1
Certification	Google EDLA certification	HDMI Cable	3m×1
RAM	8GB	USB Touch Cable (Type A-B)	3m×1
ROM	64GB	Remote Control	×1
SoC Process	8nm	Stylus	×2
CPU	A76×4+A55×4 Octa-core	Wall Mount	WIB9060G
GPU	Mali-G610 MP4	Wireless Adapter	SI07B
NPU	6 TOPS		

Optional Module	
Camera	UC W31
OPS	OPS62A/OPS72A
Sensor Box	WL10C
Mobile Stand	ST41B

Software	
System OS	MAXHUB EDU OS V4.0
Whiteboard Tool	MAXHUB Class
Screen Sharing	MAXHUB Connect
Device Management	MAXHUB Pivot
Google Apps	Google Play, Google Drive, Google Meet, Google map, YouTube, etc.
Other Apps	Browser, Cloud Drive, Note, Palette, WPS Office, etc.

Environment	
Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	10%-90% RH
Storage Humidity	10%-90% RH
Altitude	Below 5000 meters
Dust Resistance	IP5X-rated






# MAXHUB

Beyond Collaboration

 [www.maxhub.com/en/](http://www.maxhub.com/en/)

 [sales@maxhub.com](mailto:sales@maxhub.com)

 <https://www.youtube.com/c/MAXHUB>

 <https://www.facebook.com/MAXHUB.Global>

 <https://www.linkedin.com/company/maxhub-overseas/>